

[chromium](#) / [chromium](#) / [src](#) / [refs/tags/64.0.3282.24](#) / [.](#) / [components](#) / [spellcheck](#) / [browser](#) / **spelling_service_client.cc**

blob: 05567414e5825f01a40409c490765df6e79832cd [[file](#)]

```
1 // Copyright (c) 2012 The Chromium Authors. All rights reserved.
2 // Use of this source code is governed by a BSD-style license that can be
3 // found in the LICENSE file.
4
5 #include "components/spellcheck/browser/spelling_service_client.h"
6
7 #include <stddef.h>
8
9 #include <algorithm>
10
11 #include "base/json/json_reader.h"
12 #include "base/json/string_escape.h"
13 #include "base/logging.h"
14 #include "base/memory/ptr_util.h"
15 #include "base/stl_util.h"
16 #include "base/strings/string_util.h"
17 #include "base/strings/stringprintf.h"
18 #include "base/strings/utf_string_conversions.h"
19 #include "base/values.h"
20 #include "components/data_use_measurement/core/data_use_user_data.h"
21 #include "components/prefs/pref_service.h"
22 #include "components/spellcheck/browser/pref_names.h"
23 #include "components/spellcheck/common/spellcheck_common.h"
24 #include "components/spellcheck/common/spellcheck_result.h"
25 #include "components/user_prefs/user_prefs.h"
26 #include "content/public/browser/browser_context.h"
27 #include "content/public/browser/storage_partition.h"
28 #include "google_apis/google_api_keys.h"
29 #include "net/base/load_flags.h"
30 #include "net/url_request/url_fetcher.h"
31 #include "url/gurl.h"
32
33 namespace {
34
35 // The URL for requesting spell checking and sending user feedback.
36 const char kSpellingServiceURL[] = "https://www.googleapis.com/rpc";
37
38 // The location of spellcheck suggestions in JSON response from spelling
39 // service.
40 const char kMisspellingsPath[] = "result.spellingCheckResponse.misspellings";
```

```

41
42 // The location of error messages in JSON response from spelling service.
43 const char kErrorPath[] = "error";
44
45 // Languages currently supported by SPELLCHECK.
46 const char* const kValidLanguages[] = {"en", "es", "fi", "da"};
47
48 } // namespace
49
50 SpellingServiceClient::SpellingServiceClient() {}
51
52 SpellingServiceClient::~SpellingServiceClient() {}
53
54 bool SpellingServiceClient::RequestTextCheck(
55     content::BrowserContext* context,
56     ServiceType type,
57     const base::string16& text,
58     const TextCheckCompleteCallback& callback) {
59     DCHECK(type == SUGGEST || type == SPELLCHECK);
60     if (!context || !IsAvailable(context, type)) {
61         callback.Run(false, text, std::vector<SpellCheckResult>());
62         return false;
63     }
64
65     const PrefService* pref = user_prefs::UserPrefs::Get(context);
66     DCHECK(pref);
67
68     std::string dictionary;
69     pref->GetList(spellcheck::prefs::kSpellCheckDictionaries)
70         ->GetString(0, &dictionary);
71
72     std::string language_code;
73     std::string country_code;
74     spellcheck::GetISOLanguageCountryCodeFromLocale(dictionary, &language_code,
75                                                         &country_code);
76
77     // Replace typographical apostrophes with typewriter apostrophes, so that
78     // server word breaker behaves correctly.
79     const base::char16 kApostrophe = 0x27;
80     const base::char16 kRightSingleQuotationMark = 0x2019;
81     base::string16 text_copy = text;
82     std::replace(text_copy.begin(), text_copy.end(), kRightSingleQuotationMark,
83                 kApostrophe);
84
85     // Format the JSON request to be sent to the Spelling service.
86     std::string encoded_text = base::GetQuotedJSONString(text_copy);
87
88     static const char kSpellingRequest[] =
89         "{"

```

```

90     "\"method\":\"spelling.check\","
91     "\"apiVersion\":\"v%d\","
92     "\"params\":{\"
93     "\"text\":%s,\"
94     "\"language\":\"%s\","
95     "\"originCountry\":\"%s\","
96     "\"key\":\"%s"
97     "}"
98     "};
99     std::string api_key = base::GetQuotedJSONString(google_apis::GetAPIKey());
100     std::string request = base::StringPrintf(
101         kSpellingRequest, type, encoded_text.c_str(), language_code.c_str(),
102         country_code.c_str(), api_key.c_str());
103
104     GURL url = GURL(kSpellingServiceURL);
105
106     // Create traffic annotation tag.
107     net::NetworkTrafficAnnotationTag traffic_annotation =
108         net::DefineNetworkTrafficAnnotation("spellcheck_lookup", R"(
109             semantics {
110                 sender: "Online Spellcheck"
111                 description:
112                     "Chromium can provide smarter spell-checking, by sending the text "
113                     "that the users type into the browser, to Google's servers. This "
114                     "allows users to use the same spell-checking technology used by "
115                     "Google products, such as Docs. If the feature is enabled, "
116                     "Chromium will send the entire contents of text fields as user "
117                     "types them to Google, along with the browser's default language. "
118                     "Google returns a list of suggested spellings, which will be "
119                     "displayed in the context menu."
120                 trigger: "User types text into a text field or asks to correct a "
121                         "misspelled word."
122                 data: "Text a user has typed into a text field. No user identifier "
123                     "is sent along with the text."
124                 destination: GOOGLE_OWNED_SERVICE
125             }
126             policy {
127                 cookies_allowed: NO
128                 setting:
129                     "Users can enable or disable this feature via 'Use a web service "
130                     "to help resolve spelling errors.' in Chromium's settings under "
131                     "Advanced. The feature is disabled by default."
132                 chrome_policy {
133                     SpellCheckServiceEnabled {
134                         policy_options {mode: MANDATORY}
135                         SpellCheckServiceEnabled: false
136                     }
137                 }
138             })");

```

```

139
140     net::URLFetcher* fetcher =
141         CreateURLFetcher(url, traffic_annotation).release();
142     data_use_measurement::DataUseUserData::AttachToFetcher(
143         fetcher, data_use_measurement::DataUseUserData::SPELL_CHECKER);
144     fetcher->SetRequestContext(
145         content::BrowserContext::GetDefaultStoragePartition(context)
146             ->GetURLRequestContext());
147     fetcher->SetUploadData("application/json", request);
148     fetcher->SetLoadFlags(net::LOAD_DO_NOT_SEND_COOKIES |
149                          net::LOAD_DO_NOT_SAVE_COOKIES);
150     spellcheck_fetchers_[fetcher] = base::MakeUnique<TextCheckCallbackData>(
151         base::WrapUnique(fetcher), callback, text);
152     fetcher->Start();
153     return true;
154 }
155
156 bool SpellingServiceClient::IsAvailable(content::BrowserContext* context,
157                                         ServiceType type) {
158     const PrefService* pref = user_prefs::UserPrefs::Get(context);
159     DCHECK(pref);
160     // If prefs don't allow spellchecking, if the context is off the record, or if
161     // multilingual spellchecking is enabled the spelling service should be
162     // unavailable.
163     if (!pref->GetBoolean(spellcheck::prefs::kEnableSpellcheck) ||
164         !pref->GetBoolean(spellcheck::prefs::kSpellCheckUseSpellingService) ||
165         context->IsOffTheRecord())
166         return false;
167
168     // If the locale for spelling has not been set, the user has not decided to
169     // use spellcheck so we don't do anything remote (suggest or spelling).
170     std::string locale;
171     pref->GetList(spellcheck::prefs::kSpellCheckDictionaries)
172         ->GetString(0, &locale);
173     if (locale.empty())
174         return false;
175
176     // Finally, if all options are available, we only enable only SUGGEST
177     // if SPELLCHECK is not available for our language because SPELLCHECK results
178     // are a superset of SUGGEST results.
179     for (const char* language : kValidLanguages) {
180         if (!locale.compare(0, 2, language))
181             return type == SPELLCHECK;
182     }
183
184     // Only SUGGEST is allowed.
185     return type == SUGGEST;
186 }
187

```

```

188 bool SpellingServiceClient::ParseResponse(
189     const std::string& data,
190     std::vector<SpellCheckResult>* results) {
191     // When this JSON-RPC call finishes successfully, the Spelling service returns
192     // an JSON object listed below.
193     // * result - an envelope object representing the result from the APIARY
194     // server, which is the JSON-API front-end for the Spelling service. This
195     // object consists of the following variable:
196     // - spellingCheckResponse (SpellingCheckResponse).
197     // * SpellingCheckResponse - an object representing the result from the
198     // Spelling service. This object consists of the following variable:
199     // - misspellings (optional array of Misspelling)
200     // * Misspelling - an object representing a misspelling region and its
201     // suggestions. This object consists of the following variables:
202     // - charStart (number) - the beginning of the misspelled region;
203     // - charLength (number) - the length of the misspelled region;
204     // - suggestions (array of string) - the suggestions for the misspelling
205     // text, and;
206     // - canAutoCorrect (optional boolean) - whether we can use the first
207     // suggestion for auto-correction.
208     // For example, the Spelling service returns the following JSON when we send a
209     // spelling request for "duck goes quisk" as of 16 August, 2011.
210     // {
211     //   "result": {
212     //     "spellingCheckResponse": {
213     //       "misspellings": [{
214     //         "charStart": 10,
215     //         "charLength": 5,
216     //         "suggestions": [{ "suggestion": "quack" }],
217     //         "canAutoCorrect": false
218     //       }]
219     //     }
220     //   }
221     // }
222     // If the service is not available, the Spelling service returns JSON with an
223     // error.
224     // {
225     //   "error": {
226     //     "code": 400,
227     //     "message": "Bad Request",
228     //     "data": [...]
229     //   }
230     // }
231     std::unique_ptr<base::DictionaryValue> value(
232         static_cast<base::DictionaryValue*>(
233             base::JSONReader::Read(data, base::JSON_ALLOW_TRAILING_COMMAS)
234             .release()));
235     if (!value.get() || !value->is_dict())
236         return false;

```

```

237
238 // Check for errors from spelling service.
239 base::DictionaryValue* error = nullptr;
240 if (value->GetDictionary(kErrorPath, &error))
241     return false;
242
243 // Retrieve the array of Misspelling objects. When the input text does not
244 // have misspelled words, it returns an empty JSON. (In this case, its HTTP
245 // status is 200.) We just return true for this case.
246 base::ListValue* misspellings = nullptr;
247 if (!value->GetList(kMisspellingsPath, &misspellings))
248     return true;
249
250 for (size_t i = 0; i < misspellings->GetSize(); ++i) {
251     // Retrieve the i-th misspelling region and put it to the given vector. When
252     // the Spelling service sends two or more suggestions, we read only the
253     // first one because SpellCheckResult can store only one suggestion.
254     base::DictionaryValue* misspelling = nullptr;
255     if (!misspellings->GetDictionary(i, &misspelling))
256         return false;
257
258     int start = 0;
259     int length = 0;
260     base::ListValue* suggestions = nullptr;
261     if (!misspelling->GetInteger("charStart", &start) ||
262         !misspelling->GetInteger("charLength", &length) ||
263         !misspelling->GetList("suggestions", &suggestions)) {
264         return false;
265     }
266
267     base::DictionaryValue* suggestion = nullptr;
268     base::string16 replacement;
269     if (!suggestions->GetDictionary(0, &suggestion) ||
270         !suggestion->GetString("suggestion", &replacement)) {
271         return false;
272     }
273     SpellCheckResult result(SpellCheckResult::SPELLING, start, length,
274                             replacement);
275     results->push_back(result);
276 }
277 return true;
278 }
279
280 SpellingServiceClient::TextCheckCallbackData::TextCheckCallbackData(
281     std::unique_ptr<net::URLFetcher> fetcher,
282     TextCheckCompleteCallback callback,
283     base::string16 text)
284     : fetcher(std::move(fetcher)), callback(callback), text(text) {}
285

```

```
286 SpellingServiceClient::TextCheckCallbackData::~~TextCheckCallbackData() {}
287
288 void SpellingServiceClient::OnURLFetchComplete(const net::URLFetcher* source) {
289     DCHECK(base::ContainsKey(spellcheck_fetchers_, source));
290     std::unique_ptr<TextCheckCallbackData> callback_data =
291         std::move(spellcheck_fetchers_[source]);
292     spellcheck_fetchers_.erase(source);
293
294     bool success = false;
295     std::vector<SpellCheckResult> results;
296     if (source->GetResponseCode() / 100 == 2) {
297         std::string data;
298         source->GetResponseAsString(&data);
299         success = ParseResponse(data, &results);
300     }
301
302     // The callback may release the last (transitive) dependency on |this|. It
303     // MUST be the last function called.
304     callback_data->callback.Run(success, callback_data->text, results);
305 }
306
307 std::unique_ptr<net::URLFetcher> SpellingServiceClient::CreateURLFetcher(
308     const GURL& url,
309     net::NetworkTrafficAnnotationTag traffic_annotation) {
310     return net::URLFetcher::Create(url, net::URLFetcher::POST, this,
311                                     traffic_annotation);
312 }
```