

[chromium](#) / [chromium](#) / [src](#) / [refs/tags/64.0.3282.24](#) / [.](#) / [google_apis](#) / [google_api_keys.cc](#)

blob: 2e8437ed136e682540835ef4738e3519f9cb6051 [[file](#)]

```
1 // Copyright (c) 2012 The Chromium Authors. All rights reserved.
2 // Use of this source code is governed by a BSD-style license that can be
3 // found in the LICENSE file.
4
5 #include "google_apis/google_api_keys.h"
6
7 // If you add more includes to this list, you also need to add them to
8 // google_api_keys_unittest.cc.
9
10 #include <stddef.h>
11
12 #include <memory>
13
14 #include "base/command_line.h"
15 #include "base/environment.h"
16 #include "base/lazy_instance.h"
17 #include "base/logging.h"
18 #include "base/strings/stringize_macros.h"
19 #include "google_apis/gaia/gaia_switches.h"
20
21 #if defined(OS_MACOSX)
22 #include "google_apis/google_api_keys_mac.h"
23 #endif
24
25 #if defined(GOOGLE_CHROME_BUILD) || defined(USE_OFFICIAL_GOOGLE_API_KEYS)
26 #include "google_apis/internal/google_chrome_api_keys.h"
27 #endif
28
29 // Used to indicate an unset key/id/secret. This works better with
30 // various unit tests than leaving the token empty.
31 #define DUMMY_API_TOKEN "dummytoken"
32
33 #if !defined(GOOGLE_API_KEY)
34 #define GOOGLE_API_KEY DUMMY_API_TOKEN
35 #endif
36
37 #if !defined(GOOGLE_CLIENT_ID_MAIN)
38 #define GOOGLE_CLIENT_ID_MAIN DUMMY_API_TOKEN
39 #endif
40
```

```

41  #if !defined(GOOGLE_CLIENT_SECRET_MAIN)
42  #define GOOGLE_CLIENT_SECRET_MAIN DUMMY_API_TOKEN
43  #endif
44
45  #if !defined(GOOGLE_CLIENT_ID_CLOUD_PRINT)
46  #define GOOGLE_CLIENT_ID_CLOUD_PRINT DUMMY_API_TOKEN
47  #endif
48
49  #if !defined(GOOGLE_CLIENT_SECRET_CLOUD_PRINT)
50  #define GOOGLE_CLIENT_SECRET_CLOUD_PRINT DUMMY_API_TOKEN
51  #endif
52
53  #if !defined(GOOGLE_CLIENT_ID_REMOTING)
54  #define GOOGLE_CLIENT_ID_REMOTING DUMMY_API_TOKEN
55  #endif
56
57  #if !defined(GOOGLE_CLIENT_SECRET_REMOTING)
58  #define GOOGLE_CLIENT_SECRET_REMOTING DUMMY_API_TOKEN
59  #endif
60
61  #if !defined(GOOGLE_CLIENT_ID_REMOTING_HOST)
62  #define GOOGLE_CLIENT_ID_REMOTING_HOST DUMMY_API_TOKEN
63  #endif
64
65  #if !defined(GOOGLE_CLIENT_SECRET_REMOTING_HOST)
66  #define GOOGLE_CLIENT_SECRET_REMOTING_HOST DUMMY_API_TOKEN
67  #endif
68
69  // This is really the API key for non-stable channels on Android. It's
70  // named after the first feature that used it.
71  // TODO(jkrca,rogerta): Rename this to GOOGLE_API_KEY_ANDROID_NON_STABLE.
72  #if !defined(GOOGLE_API_KEY_PHYSICAL_WEB_TEST)
73  #define GOOGLE_API_KEY_PHYSICAL_WEB_TEST DUMMY_API_TOKEN
74  #endif
75
76  // These are used as shortcuts for developers and users providing
77  // OAuth credentials via preprocessor defines or environment
78  // variables. If set, they will be used to replace any of the client
79  // IDs and secrets above that have not been set (and only those; they
80  // will not override already-set values).
81  #if !defined(GOOGLE_DEFAULT_CLIENT_ID)
82  #define GOOGLE_DEFAULT_CLIENT_ID ""
83  #endif
84  #if !defined(GOOGLE_DEFAULT_CLIENT_SECRET)
85  #define GOOGLE_DEFAULT_CLIENT_SECRET ""
86  #endif
87
88  namespace google_apis {
89

```

```
90  const char kAPIKeysDevelopersHowToURL[] =
91      "http://www.chromium.org/developers/how-tos/api-keys";
92
93  // This is used as a lazy instance to determine keys once and cache them.
94  class APIKeyCache {
95  public:
96      APIKeyCache() {
97          std::unique_ptr<base::Environment> environment(base::Environment::Create());
98          base::CommandLine* command_line = base::CommandLine::ForCurrentProcess();
99
100         api_key_ = CalculateKeyValue(
101             GOOGLE_API_KEY, STRINGIZE_NO_EXPANSION(GOOGLE_API_KEY), NULL,
102             std::string(), environment.get(), command_line);
103
104         // A special non-stable key is at the moment defined only for Android Chrome.
105         #if defined(OS_ANDROID)
106             api_key_non_stable_ = CalculateKeyValue(
107                 GOOGLE_API_KEY_PHYSICAL_WEB_TEST,
108                 STRINGIZE_NO_EXPANSION(GOOGLE_API_KEY_PHYSICAL_WEB_TEST), NULL,
109                 std::string(), environment.get(), command_line);
110         #else
111             api_key_non_stable_ = api_key_;
112         #endif
113
114         std::string default_client_id =
115             CalculateKeyValue(GOOGLE_DEFAULT_CLIENT_ID,
116                             STRINGIZE_NO_EXPANSION(GOOGLE_DEFAULT_CLIENT_ID),
117                             NULL,
118                             std::string(),
119                             environment.get(),
120                             command_line);
121         std::string default_client_secret =
122             CalculateKeyValue(GOOGLE_DEFAULT_CLIENT_SECRET,
123                             STRINGIZE_NO_EXPANSION(GOOGLE_DEFAULT_CLIENT_SECRET),
124                             NULL,
125                             std::string(),
126                             environment.get(),
127                             command_line);
128
129         // We currently only allow overriding the baked-in values for the
130         // default OAuth2 client ID and secret using a command-line
131         // argument, since that is useful to enable testing against
132         // staging servers, and since that was what was possible and
133         // likely practiced by the QA team before this implementation was
134         // written.
135         client_ids_[CLIENT_MAIN] = CalculateKeyValue(
136             GOOGLE_CLIENT_ID_MAIN,
137             STRINGIZE_NO_EXPANSION(GOOGLE_CLIENT_ID_MAIN),
138             switches::kOAuth2ClientID,
```

```
139         default_client_id,  
140         environment.get(),  
141         command_line);  
142     client_secrets_[CLIENT_MAIN] = CalculateKeyValue(  
143         GOOGLE_CLIENT_SECRET_MAIN,  
144         STRINGIZE_NO_EXPANSION(GOOGLE_CLIENT_SECRET_MAIN),  
145         switches::kOAuth2ClientSecret,  
146         default_client_secret,  
147         environment.get(),  
148         command_line);  
149  
150     client_ids_[CLIENT_CLOUD_PRINT] = CalculateKeyValue(  
151         GOOGLE_CLIENT_ID_CLOUD_PRINT,  
152         STRINGIZE_NO_EXPANSION(GOOGLE_CLIENT_ID_CLOUD_PRINT),  
153         NULL,  
154         default_client_id,  
155         environment.get(),  
156         command_line);  
157     client_secrets_[CLIENT_CLOUD_PRINT] = CalculateKeyValue(  
158         GOOGLE_CLIENT_SECRET_CLOUD_PRINT,  
159         STRINGIZE_NO_EXPANSION(GOOGLE_CLIENT_SECRET_CLOUD_PRINT),  
160         NULL,  
161         default_client_secret,  
162         environment.get(),  
163         command_line);  
164  
165     client_ids_[CLIENT_REMOTING] = CalculateKeyValue(  
166         GOOGLE_CLIENT_ID_REMOTING,  
167         STRINGIZE_NO_EXPANSION(GOOGLE_CLIENT_ID_REMOTING),  
168         NULL,  
169         default_client_id,  
170         environment.get(),  
171         command_line);  
172     client_secrets_[CLIENT_REMOTING] = CalculateKeyValue(  
173         GOOGLE_CLIENT_SECRET_REMOTING,  
174         STRINGIZE_NO_EXPANSION(GOOGLE_CLIENT_SECRET_REMOTING),  
175         NULL,  
176         default_client_secret,  
177         environment.get(),  
178         command_line);  
179  
180     client_ids_[CLIENT_REMOTING_HOST] = CalculateKeyValue(  
181         GOOGLE_CLIENT_ID_REMOTING_HOST,  
182         STRINGIZE_NO_EXPANSION(GOOGLE_CLIENT_ID_REMOTING_HOST),  
183         NULL,  
184         default_client_id,  
185         environment.get(),  
186         command_line);  
187     client_secrets_[CLIENT_REMOTING_HOST] = CalculateKeyValue(  

```

```

188     GOOGLE_CLIENT_SECRET_REMOTING_HOST,
189     STRINGIZE_NO_EXPANSION(GOOGLE_CLIENT_SECRET_REMOTING_HOST),
190     NULL,
191     default_client_secret,
192     environment.get(),
193     command_line);
194 }
195
196     std::string api_key() const { return api_key_; }
197 #if defined(OS_IOS)
198     void set_api_key(const std::string& api_key) { api_key_ = api_key; }
199 #endif
200     std::string api_key_non_stable() const { return api_key_non_stable_; }
201
202     std::string GetClientID(OAuth2Client client) const {
203         DCHECK_LT(client, CLIENT_NUM_ITEMS);
204         return client_ids_[client];
205     }
206
207 #if defined(OS_IOS)
208     void SetClientID(OAuth2Client client, const std::string& client_id) {
209         client_ids_[client] = client_id;
210     }
211 #endif
212
213     std::string GetClientSecret(OAuth2Client client) const {
214         DCHECK_LT(client, CLIENT_NUM_ITEMS);
215         return client_secrets_[client];
216     }
217
218 #if defined(OS_IOS)
219     void SetClientSecret(OAuth2Client client, const std::string& client_secret) {
220         client_secrets_[client] = client_secret;
221     }
222 #endif
223
224     std::string GetSpdyProxyAuthValue() {
225 #if defined(SPDY_PROXY_AUTH_VALUE)
226         return SPDY_PROXY_AUTH_VALUE;
227 #else
228         return std::string();
229 #endif
230     }
231
232 private:
233     // Gets a value for a key. In priority order, this will be the value
234     // provided via a command-line switch, the value provided via an
235     // environment variable, or finally a value baked into the build.
236     // |command_line_switch| may be NULL. Official Google Chrome builds will not

```

```

237 // use the value provided by an environment variable.
238 static std::string CalculateKeyValue(const char* baked_in_value,
239                                     const char* environment_variable_name,
240                                     const char* command_line_switch,
241                                     const std::string& default_if_unset,
242                                     base::Environment* environment,
243                                     base::CommandLine* command_line) {
244     std::string key_value = baked_in_value;
245     std::string temp;
246     #if defined(OS_MACOSX)
247         // macOS and iOS can also override the API key with a value from the
248         // Info.plist.
249         temp = ::google_apis::GetAPIKeyFromInfoPlist(environment_variable_name);
250         if (!temp.empty()) {
251             key_value = temp;
252             VLOG(1) << "Overriding API key " << environment_variable_name
253                 << " with value " << key_value << " from Info.plist.";
254         }
255     #endif
256
257     #if !defined(GOOGLE_CHROME_BUILD)
258         // Don't allow using the environment to override API keys for official
259         // Google Chrome builds. There have been reports of mangled environments
260         // affecting users (crbug.com/710575).
261         if (environment->GetVar(environment_variable_name, &temp)) {
262             key_value = temp;
263             VLOG(1) << "Overriding API key " << environment_variable_name
264                 << " with value " << key_value << " from environment variable.";
265         }
266     #endif
267
268     if (command_line_switch && command_line->HasSwitch(command_line_switch)) {
269         key_value = command_line->GetSwitchValueASCII(command_line_switch);
270         VLOG(1) << "Overriding API key " << environment_variable_name
271             << " with value " << key_value << " from command-line switch.";
272     }
273
274     if (key_value == DUMMY_API_TOKEN) {
275     #if defined(GOOGLE_CHROME_BUILD)
276         // No key should be unset in an official build except the
277         // GOOGLE_DEFAULT_* keys. The default keys don't trigger this
278         // check as their "unset" value is not DUMMY_API_TOKEN.
279         CHECK(false);
280     #endif
281         if (default_if_unset.size() > 0) {
282             VLOG(1) << "Using default value \"" << default_if_unset
283                 << "\" for API key " << environment_variable_name;
284             key_value = default_if_unset;
285         }

```

```
286     }
287
288     // This should remain a debug-only log.
289     DVLOG(1) << "API key " << environment_variable_name << "=" << key_value;
290
291     return key_value;
292 }
293
294 std::string api_key_;
295 std::string api_key_non_stable_;
296 std::string client_ids_[CLIENT_NUM_ITEMS];
297 std::string client_secrets_[CLIENT_NUM_ITEMS];
298 };
299
300 static base::LazyInstance<APIKeyCache>::DestructorAtExit g_api_key_cache =
301     LAZY_INSTANCE_INITIALIZER;
302
303 bool HasKeysConfigured() {
304     if (GetAPIKey() == DUMMY_API_TOKEN)
305         return false;
306
307     for (size_t client_id = 0; client_id < CLIENT_NUM_ITEMS; ++client_id) {
308         OAuth2Client client = static_cast<OAuth2Client>(client_id);
309         if (GetOAuth2ClientID(client) == DUMMY_API_TOKEN ||
310             GetOAuth2ClientSecret(client) == DUMMY_API_TOKEN) {
311             return false;
312         }
313     }
314
315     return true;
316 }
317
318 std::string GetAPIKey() {
319     return g_api_key_cache.Get().api_key();
320 }
321
322 std::string GetNonStableAPIKey() {
323     return g_api_key_cache.Get().api_key_non_stable();
324 }
325
326 #if defined(OS_IOS)
327 void SetAPIKey(const std::string& api_key) {
328     g_api_key_cache.Get().set_api_key(api_key);
329 }
330 #endif
331
332 std::string GetOAuth2ClientID(OAuth2Client client) {
333     return g_api_key_cache.Get().GetClientID(client);
334 }
```

```

335
336 std::string GetOAuth2ClientSecret(OAuth2Client client) {
337     return g_api_key_cache.Get().GetClientSecret(client);
338 }
339
340 #if defined(OS_IOS)
341 void SetOAuth2ClientID(OAuth2Client client, const std::string& client_id) {
342     g_api_key_cache.Get().SetClientID(client, client_id);
343 }
344
345 void SetOAuth2ClientSecret(OAuth2Client client,
346                             const std::string& client_secret) {
347     g_api_key_cache.Get().SetClientSecret(client, client_secret);
348 }
349 #endif
350
351 std::string GetSpdyProxyAuthValue() {
352     return g_api_key_cache.Get().GetSpdyProxyAuthValue();
353 }
354
355 bool IsGoogleChromeAPIKeyUsed() {
356     #if defined(GOOGLE_CHROME_BUILD) || defined(USE_OFFICIAL_GOOGLE_API_KEYS)
357         return true;
358     #else
359         return false;
360     #endif
361 }
362
363 } // namespace google_apis

```